

SYSTEM 4000-S660



The smallest long stroke unit of the range, offers a real flexibility with a wide configuration's option. From mono cavity to 8 cavities with a quick mould change, represent the ideal EBM for short run with high quality products requirements.

To be noticed that tooling are completely interchangeable with the SYSTEM 4000 T 660, and this important feature contribute to the "flexibility system concept".

In addition, the small footprint of this equipment makes the layout easy at any factory structure.

CAVITY NUMBER	N°	10	9	8	7	6	5	4	3	2
CENTER DISTANCE	mm	60	67.5	75	85	100	120	150	200	300

MOULD CARRIAGE STROKE = 660 mm

S/Ø	Bottle (S dimension) OR Ø	Bmax (mm)	150
H	Bottles height	max (mm)	320
A	Mould max height	(mm)	450
C	Mould max length	(mm)	690
B	Half mould width	max (mm)	130
	Dry cycle time	sec	2.2
	Clamping force	kN	180
	Extruder capacity	kg/h	160

MONO PE-PP	●
MONO PVC	
MONO HMWPE	
COEX-2	●
COEX-3	●
COEX-4	
COEX-5	
COEX-6	
I.M.L.	

SYSTEM 4000-T660



A real high productivity machine, with maximum 20 cavities offers low consumption energy while accommodate a wide range of products, from personal care to household chemicals.

All units are equipped with quick mould and color change and all major option are available, such as window stripe, co-extrusion up to 3 layers, inclined neck, leak tester.

productivity world-wide and sold in all 5 continents, offers a very short return of investment timing with a low level of maintenance costs.

CAVITY NUMBER	2xN°	10	9	8	7	6	5	4	3	2
CENTER DISTANCE	mm	60	67.5	75	85	100	120	150	200	300

MOULD CARRIAGE STROKE = 660 mm

S/Ø	Bottle (S dimension) OR Ø	Bmax (mm)	150
H	Bottles height	max (mm)	320
A	Mould max height	(mm)	450
C	Mould max length	(mm)	690
B	Half mould width	max (mm)	130
	Dry cycle time	sec	2.4
	Clamping force	kN	180
	Extruder capacity	kg/h	160

MONO PE-PP	●
MONO PVC	
MONO HMWPE	
COEX-2	●
COEX-3	●
COEX-4	
COEX-5	
COEX-6	
I.M.L.	